

REVLAR®

Waterproof Synthetic Paper

Premium Labels

These labels are waterproof, tear-proof, durable, impervious to grease and chemicals, weatherproof and specifically designed to withstand high/low temperature fluctuations.

REVLAR is perfect for wet, harsh and outdoor environments.



REVLAR Premium Labels are a durable material with adhesive and paper liner and come in removable and permanent versions

Waterproof removable labels

Low Tack Removable Labels

- Repositionable, removable, reusable
 - Unique physical structure in which large particles limit physical contact with the surface, forming a discontinuous film.
- Uses include signage, price tags

Item No.	Thickness	Weight	8.5" x 11"	12" x 18"
504WVMA	4 mil	294 gsm	•	•

Temperatures

- Label can be applied at 50°+ Fahrenheit
- Once applied, adhesive will hold from -40° to 176° Fahrenheit

Waterproof permanent labels

Permanent Waterproof Labels

- Long-lasting adhesive to guarantee your label will stay in place
- Uses include bottle labeling, package labeling and permanent signage

Item No.	Thickness	Weight	Finish	8.5" x 11"	12" x 18"
502D	2 mil	198 gsm	Gloss	•	•
502E	2 mil	198 gsm	Matte	•	•
502F	2 mil	198 gsm	Clear	•	•

About Relyco:

For almost 30 years, Relyco has been the premier supplier of unique and innovative paper products.

Our products are great for thousands of uses, which enables you to get the most value out of your printer investment. Understanding and meeting our clients' needs is always our first priority.

Contact us:

www.relyco.com
(800) 777-7359



Continue...

Waterproof permanent labels (continued)

Marine & Laboratory Grade Labels

- Industry's most durable labeling products available
- Certified for British Maritime Standard 5609:1986 Section 2 and 3 marine and laboratory immersion
 - Testing completed by Smithers Pira
 - Includes a 3-month exposure in salt water at mid-tide and standard laboratory conditions
 - Testing for abrasion resistance, adhesion and durability of print including fading, color changes and symbol identification
- Designed to withstand wash-downs as well as total seawater immersion
- Uses include chemical drum labels, drums and containers used to transport petroleum, paint, liquid or powder chemicals

Item No.	Thickness	Weight	8.5" x 11"	12" x 18"
502MGDL	2 mil	245 gsm	•	•

Temperatures



- Label can be applied between 41° to 122° Fahrenheit
- Once applied, adhesive will hold from -40° to 158° Fahrenheit

How is the printability for REVLAR Premium Labels?

- Tested and certified to run smoothly on all major OEM dry toner laser printers
- Also compatible with offset and flexo printers

Pro tips for best results:



- Allow the paper to acclimate to the printer's room for 24 hours prior to printing
- Reduce static by fanning the sheets on all edges prior to printing
- Use printer settings that keep fuser temperature low and run sheets slowly
- Maintain a straight paper path through the printer if possible

Features

- Melting Point - >400° Fahrenheit
- Easy peel corners



Classified as a #7 plastic. Can be recycled as a plastic, not as a paper. Check with your local recycling services for options.